

Special & Hot Farm Class Rules:

All classes will be limited to 3000 RPMs. **(All must have working air shut-off)**

7500 Special – “A” Pump allowed, Maximum 320 ci, Maximum 2.4 Turbo (box turbo), 4 or 6 cyl, Water injection or inner cooler not both, Max tire size 18.4.38 (top cut only)

8500 Hot Farm – “A” or “P” Pump allowed, Maximum 426ci, Maximum 2.6 Turbo (box turbo), Water injection or inner cooler not both, Max tire size 20.8.38 (top cut only)

11000 to 14000 Hot Farm – “A” or “P” Pump allowed, Maximum 640 ci, Maximum 3.0” Turbo, Max tire size 20.8.42 or 24.5.32 (top cut only)

10000 (18 MPH) – Maximum 480ci, 2.8 Turbo (box turbo), Max Tire size 20.8.42 (top cut only) Required: Roll Guard, Frame connectors, Seatbelt, Helmet, Fire Jacket, and Working Air Shut-off.

The following Safety Equipment is required for 7500 Special, 8500 Hot Farm, 11000 to 14000 Hot Farm Classes:

- Roll Guard (can be homemade with 3” heavy wall metal) or Full Roll Cage
- Frame Connectors
- Seatbelt
- Helmet & Fire Jacket (Long Pants)
- Steel Flywheel (Prove it is steel)
- Scatter Blanket
- Working Air Shut-off
- Wheelie Skids

: